DC charging cables PURWIL HPC UL

211_UL

Robust and flexible polyurethane charging cable with control wires and optimized outer diameter

Application

For the connection of the electric car to the charging outlet.

Construction

Control wires:
- Cu conductor AWG 18, bare (IEC 60228)
- Core insulation made of EPR
- Core color: white, numbered

Power cores:
- Cu-conductor AWG (Kl.6), bare (IEC 60228)
- Core insulation made of cross-linked HEPR
- Core colors black, red, green-yellow

Cable:
- Power cores stranded with the control wires and fillers
- Jacket material made of flame retardant polyurethane (PUR-FRNC)

Jacket colour

Black similar to RAL 9005

Description

- Sheath with improved flexibility
- high mechanical strength
- good cold flexibility
- good oil and fuel resistance
- UV, ozone and weather resistant
- min. bending radius 10 x D dynamic (D = cable Ø)
- halogen-free
- flame retardant

Electrical data

Signal wires:
- Nominal voltage: Uo/U 600 / 1.000 V
- Test voltage: 3.500 V / 50 Hz

Power cores:
- Nominal voltage: Uo/U 600 / 1.000 V
- Test voltage: 3.500 V / 50 Hz

Temperature range

- -40 °C to +90 °C
- in case of a short circuit up to 160 °C for 5s

Standards

UL recognized E530622
IEC 60754-1 Halogen free
IEC 60754-2 No corrosive gases

Technical data

Cross-section AWG	Part no.	Conductor code	Current carrying capacity at 40°C ambient temperature A	Ø D mm	Copper index kg/km	Weight kg/km
2x 2/0 + 1G2 + [8x 18 C]	822311	2LPE+8L	250	34.4 ± 0.4	1737.6	2217
2x [2x 1] + 1G1 + [8x 18 C]	822312	2LPE+8L	375	40.5 ± 0.4	2457.6	3119

Subject to change without notice

BRUGG eConnect
BRUGG eConnect
info.econnect@brugg.com