

Assembled charging connector

PURWIL HPC CCS2 CLASSIC 375

DC high-power charging cable with CCS2 connector for fast charging of electric vehicles using direct current (DC). The robust CCS2 charging connector, combined with the durable PUR (polyurethane) DC cable, provides an ideal solution for long-lasting and efficient performance under demanding outdoor conditions.

Rated current (at 40 °C) : 375 A*

Boost Mode (15 minutes at 40 °C) : 600 A

Rated voltage : 1'000 V DC

CCS2 Connector Classic

- Charging standard : CCS Type 2
- IP Rating : IP67
- Proximity pilot resistant : 1'500 Ω (between PE and PP)
- Ambient temperature (operation) : -30 °C to +40 °C (Higher ambient temperature possible with current reduction required, observe temperature limit at DC contacts of 90 °C)
- Temperature monitoring : 2x PT1000
- Insertion / withdrawal cycles : >10'000
- Contacts : replaceable
- Front face : replaceable

DC charging cable PURWIL HPC 375

- Possible cable length : Up to 10 m
- Execution : one end assembled with CCS2 Classic charging plug
- Second end assembly : possible on request
- Cross-section: 2x [2x 55] + 1G35 + 4x [2x 0.75]
- Cable weight : 3.10 kg/m
- Outer diameter : 38,5 \pm 0.5 mm
- Bending radius : 10 x D
- Temperature range : -40 °C to +90 °C

Standards

IEC 62893-4-1:2020

IEC 62196-1:2022 certified

IEC 62196-3:2022 certified

Remarks

Restrictive temperature limits : max. 90 °C (DC contacts), max. 85 °C (cable insulation)

*360 A in No-Load Endurance Test according to IEC 62196-1:2022

2413_375_Classic



Assembled charging connector

Charge Capacity

Ambient temperature (operation) °C	Current A	15 Min Boost A
30	409	657
35	392	629
40	375	600
45	355	569
50	334	536
55	313	502
60	289	464

Technical information valid for products with manufacturing number PO26-XXXX and onwards

